

# GreenCoat® Hiarc Max

GreenCoat® Hiarc Max is a patented colour coated system developed by SSAB Swedish Steel. The coating offers superior performance for roofing, cladding and internal applications that are in aggressive environments.

## Colour Range

Extensive Colour Range  
Bespoke Colour Match Available\*\*

## Usage

External Profiles  
Internal Profiles  
Flashings & Fabrications  
Flat Sheets  
  
Temporary Film Protection (Optional) Available

## Coating Specification



Coating Supplier  
Coating Type  
Coating Warranty  
Material Thickness  
Coating Thickness  
Backing Coat Thickness  
Gloss Level  
Appearance / Embossment  
Zinc Coating  
Steel Grade  
Maximum Operating Temperature

## Test standard

SSAB Swedish Steel  
GreenCoat® Hiarc Max  
40 Years  
0.5mm/0.7mm  
40 Microns  
12 Microns  
35-40GU  
Light Grain  
Z275  
S280  
110 Degrees

## Coating Performance

Corrosion Resistance Category  
UV Resistance  
European Fire Classification  
Adhesion of coating (T-bend)  
Resistance to cracking on bending (T-bend)  
Scratch Resistance

## Test standard

EN 10169  
EN 10169  
EN 13501-1  
EN 13523-7  
EN 13523-7  
EN 13523-12

## Coating Performance

RC5  
RUV5  
A1  
≤ 1 T  
≤ 1 T  
35N

\*Warranty is available up to 40 years. Terms and conditions apply.  
\*\*Subject to Quantities