Mission XP40°

A 40 year warranted coating specifically developed for severe external building applications, this product meets the enhanced requirements for aesthetic quality along with increased coating performance such as surface UV resistance, corrosion resistance and adhesion resistance.

Colour Range

Extensive Colour Range
Bespoke Colour Match Available**

Usage

External Profiles
Flashings & Fabrications
Flat Sheets

Coating Specification



Coating Type
Coating Warranty
Material Thickness
Coating Thickness
Backing Coat Thickness
Gloss Level
Appearance / Embossment
Zinc Coating
Steel Grade

Maximum Operating Temperature

Test standard	
	High Performance
	40 years**
	0.5mm / 0.7mm
EN 13523-1	200 Micron Plastisol
EN 13523-1	7 Microns Backing Coat
EN 13523-2	10-35GU
	Steon® Embossment
	ZM180 GIX
	S280
	60 Degrees

Coating Performance

Corrosion Resistance Category
UV Resistance
European Fire Classification
Adhesion Cross Harch
Adhesion of coating (T-bend)
Salt Spray Test
Scratch Resistance
Abrasion Resistance
Humidity Resistance

Test	stand	lard

EN 10169

EN 10169	
EN 13501-1	
EN 13523-6	
EN 13523-7	
EN 13523-8	
EN 13523-12	
EN 13523-16	
EN 13523-25	

Coating Performance

Coating Periormance	
RC5	
RUV4	
C, s2, d0	
100%	
OT (16*C) 1T (0*C)	
1000 Hours	
7kg	
<7mg	
1500 Hours	



*Warranty is available up to 40 years. Terms and conditions apply. **Subject to Quantities



